



HIGH DUMPING BUCKETS

UFO:s High dumping buckets are suitable for materials with a volumetric weight of 800 to 1000 kg/m³ (Wood-chips, sawdust, peat, coal, etc.). The buckets are equipped with dumping cylinders located in the sidewalls. This design has many advantages. The risk that wood chips will freeze to the bucket is minimal as no beams or other parts protrude inside the bucket. The bucket empties completely, regardless of the material being handled, and the penetration depth when loading increases. The emptying height is increased by about 1500 mm.

- The buckets are available with or without bolt-on edges.
- Dumping angle: 90°.
- Hydraulic cylinders equipped with end cushion.

Art. No.	Volume m ³	Width mm	Height mm	Depth mm	Weight kg	Max volume-weight kg/m ³
300252500	2,5	2500	1070	1230	1500	1000
300352500	3,5	2500	1410	1460	1660	1000
300552750	5,5	2750	1680	1770	2200	1000
300603000	6,0	3000	1680	1770	2220	1000
300703000	7,0	3000	1920	1800	2440	1000
300803000	8,0	3000	2100	1910	3190	1000
300903200	9,0	3200	2100	1950	3340	1000
301003200	10,0	3200	2130	1950	3550	1000
301103400	11,0	3400	2250	2040	4090	1000
301203700	12,0	3700	2250	2040	4250	800
301304000	13,0	4000	2250	2040	4540	800
301504000	15,0	4000	2590	2220	5860	800
301804000	18,0	4000	2400	2500	6110	800
302004000	20,0	4000	2640	2520	6300	800

UMEÅ FÖRSÄLJNING AB
 Läringsgatan 8. SE-904 22 Umeå
 Phone: +46 90 12 07 70
 Fax: +46 90 12 00 08

E-mail: info@ufoab.se
www.ufoab.se